

LetterPro 3 in 1 Photopolymer Platemaker

for all Waterwashout Flexographic & Letterpress Plates



Avflex

GLOBAL TECHNOLOGY – LOCAL SERVICE



**POWERFUL.
EFFECTIVE.
READY TO USE.**

The LetterPro is a complete platemaking system especially designed for water-washable letterpress plates. It encompasses the entire plate handling process including plate exposure, wash-out, drying and post-exposure.

All LetterPro functions are controlled by an integrated microprocessor. The touch-membrane keypad with digital display provides easy access to all parameters of the main equipment functions, and the ability to store nine different programs for individual plate types.

The LetterPro requires a minimum of maintenance and is the ideal solution for users with low-to-medium daily plate volume usage.



High power 40W UV-A lamps are used in both the main exposure and the post exposure section.



The dryer drawer provides drying functionality as well as post exposure.



Simple hardware controls and standard components require a minimum of maintenance effort.



The tank is designed with smooth walls only containing the heating element and a few sensors. This allows very easy cleaning of the tank.

GLUNZ & JENSEN

work positive

LetterPro 3 in 1 Photopolymer Platemaker

for all Waterwashout Flexographic & Letterpress Plates



Avflex
GLOBAL TECHNOLOGY – LOCAL SERVICE



Simple connection points at the back side of the unit.



The LetterPro is delivered with a flat brush. The brush is mounted on springs in order to secure an even brush pressure for different printing plate thicknesses.



The plate holder is magnetic and rotating in both directions at a fixed speed. Optionally, a special plate holder can be delivered for film-based printing plates.



	LetterPro	
MODEL	140 C	200 C
PERFORMANCE		
Plate types	Water-washable Letterpress plates, metal-based or film-based.	
Plate width (max)	500mm (19.7")	700mm (27.6")
Plate length (min)	350mm (13.8")	500mm (19.7")
Plate thickness	0,43mm (0.017") to 2,3mm (0.091")	
CONSUMPTION		
Power supply	1W+N+PE, 230VAC	
Power consumption	2,2kW	4kW
GENERAL		
Dimensions, equipment (LxWxH)	750 x 710 x 980mm (29.5 x 28 x 38.6")	1050 x 880 x 1040mm (41.3 x 34.6 x 41.1")
Weight, equipment	98kg (216lbs)	219kg (483lbs)
Dimensions, crate (LxWxH)	900 x 730 x 108mm (35.4 x 28.7 x 42.5")	1030 x 1100 x 1240mm (40.6 x 43.3 x 48.8")
Weight, equipment + crate	144kg (318lb)	287kg (633lb)
Tank volume	19,5 litres	50 liters
Options	Sticky plate holder for film-based printing plates. Special brush types on request.	

Note: Standard configurations may vary in the market. Specifications are subject to changes without prior notice.

Exclusive to Avflex Australia

108-110 Carnarvon Street Silverwater NSW 2128

www.grogangroup.com

GLUNZ & JENSEN

www.glunz-jensen.com

Part no. 1006514C 09/09 - 2016