


Product:	Druma-floor NC/SR	
Sound reduction:	RW 34 dB	
Thickness:	17 mm	
Size:	2400 x 600 mm	
System weight:	17,8 kg/m <sup>2</sup>	
Core material:	Calcium silicate, rot-, moisture- and impact resistant	
Certification:	B15 class according to IMO Res. 754 (18)	
Application:	Sound reduction floating floor in combination with Bisco	

This panel, with an RW of 34 dB, is composed of a calcium silicate core material, with on both sides an aluminum skin which is bonded with a special sound insulating glue.

The panels are grooved on all four sides and can be connected with an aluminum spline 38x3 mm and can be fixed with an aluminum countersunk rivet.

#### Properties:

- Meets IMO Res. 754 (18) requirements,
- Floating Floor (in combination with Bisco),
- Easy installation, no special tooling ,
- Excellent mechanical properties,
- Weight and sound reduction similar to conventional sandwich panels.

#### Installation and handling:

The panels are supplied with heavy synthetic corner protectors and are pre-drilled all round. After placing the panels and the aluminum splines, the splines just need to be drilled (hole diameter 4,5 mm). Hereafter the panels can be fixed with the supplied thread-forming screws (M 5x12 mm).

It is recommended to cover the floor with hardboard panels after installation to prevent serious damage. On request we also deliver Cover Guard; a fire resistant plastic protection film with anti-slip structure, which can cover the entire floor (comes on a roll (110 x 0,91m)). This will make sure that sparks from welding, burning of grinding do not cause risk of fire.

