



Avflex

GLOBAL TECHNOLOGY – LOCAL SERVICE

Polymount Stereo Mount

Polymount is range of a precision extruded films specifically selected for affixing Photopolymer Printing plates to, in production of Mid & Wide-Web Printing Cliché/Stereo's/Base Boards in Corrugated and Flexographic printing.

The high purity PET & PP is produced to very tight tolerances and provides high tensile strength, heat and chemical resistance. Polymount is long life and will not deteriorate under extreme conditions. Ideally suited to both flatbed or machine plate mounting, Polymount exhibits excellent antistatic properties and HF700 is available with Corona treatment to provide optimum Dyne level for improved adhesion and strong bonding of plates. Polymount is transparent in appearance to allow more accurate plate positioning.

Features and Benefits:

- High tensile strength
- High visual clarity
- Dimensionally stable
- Corona treatment for maximum adhesion
- High Chemical Resistance
- Produced to very tight tolerances.
- Excellent Antistatic properties
- 3 Popular Thickness Gauges



Technical Properties	Polymount TLS10#188	Polymount LE#250	Polymount HF#700
Thickness	0.188mm/ .007"	0.25mm/ .010"	0.7mm/ .028"
Material	Polyester	Polyester	Polypropylene
Tensile Strength	17	18	35
Elongation at Break	184	195	500
Colour	Clear	Clear	Translucent
Standard Widths	1650 & 1800mm	1650mm	1620 & 1830mm



1300 859 960



salesav@grogangroup.com

Avflex Australia, 108-110 Carnarvon St, Silverwater NSW 2128



Avflex

GLOBAL TECHNOLOGY – LOCAL SERVICE

www.grogangroup.com