


## CELLO® ADHESIVE TAPES


**Cello® ADHESIVE TAPES** are used for sealing edges, protecting components and certain surface areas that are susceptible to damage, or covering joints, seams or tears.

Basis of adhesive: Acrylate

For easy application, all adhesive tapes are available with divided non-stick liner (SPL). Width: 40, 50, 60 mm.



Example: ALU-01 **SPL**




Cello® ADHESIVE TAPES

### TECHNICAL DATA


<b>FLAMMABILITY</b>	<ul style="list-style-type: none"> <li>▶ FMVSS 302, DIN 75 200, fulfilled</li> <li>▶ ISO 3795, burning rate &lt; 100 mm/min</li> </ul>
<b>TEMPERATURE RESISTANCE</b>	-40°C to +150°C -40°C to +200°C (Cello® ALU-01)
<b>ADHESIVE STRENGTH / CPA-4.01</b>	Self-adhesive layer on steel plate: at least 35 N / 5 cm
<b>BENEFITS</b>	<ul style="list-style-type: none"> <li>▶ Excellent adhesion on a wide range of substrates</li> <li>▶ High flexibility for effortless application around edges</li> <li>▶ Easy and fast fixation</li> </ul>

### DIMENSIONS


PRODUCT	THICKNESS [mm]	WIDTH [mm]	RUNNING LENGTH	RECOMMENDED TAPE WIDTHS FOR EDGE SEALING
ALU-01 / ALU-04	0.3 ± 0.1	40, 50, 60, 70 ± 2	33 m / reel	Material thickness 10 mm --> 40 mm wide tape
PUR-01 / PUR-03	0.3 ± 0.1			Material thickness 20 mm --> 50 mm wide tape
VLC-01 / VL-53	0.9 ± 0.1			Material thickness 30 mm --> 60 mm wide tape
				Material thickness 40 mm --> 70 mm wide tape




Cello® ALU-01




Cello® ALU-04



Cello® PUR-01



Cello® PUR-03




Cello® VLC-01



Cello® VL-53

## CELLO® ADHESIVE TAPES

PRODUCT	DESCRIPTION	ELONGATION AT BREAK / ISO 9073-3 Elongation of a test piece at breaking force	BREAKING FORCE / ISO 9073-3 Maximum force applied during the elongation-to-break test
ALU-01	Aluminum tape, embossed silver-colored and scrim reinforcement for added tensile strength	approx. 4%	at least 150 N
ALU-04	Aluminum tape, smooth silver-colored and scrim reinforcement for added tensile strength	approx. 2%	at least 200 N
PUR-01	Film tape, black, with scrim reinforcement to prevent elongation	approx. 25%	at least 50 N
PUR-03	Film tape, white, with scrim reinforcement to prevent elongation	approx. 25%	at least 50 N
VLC-01	Non-woven tape: black, with scrim reinforcement to prevent elongation	approx. 25%	at least 50 N
VL-53	Non-woven tape: anthracite, with scrim reinforcement to prevent elongation	approx. 25%	at least 400 N



Cello® HR 290 ALG-04, edges covered with Cello® ALU-04



Cello® 451, edges covered with Cello® VLC-01